

S. No	Name of items	Qty
(i)	SS304 body cylinder regulator with SS diaphragm. Single stage manifold system for CO2 gas, SS braided flexible pigtails (1 mm long) complete with 5/8" end fittings with SS gas manifold. Genetic valve with pressure gauge, PVC casting patty, SS tubes (app 50 feet) (1/4" OD, 0.9 mm thickness) tubing with pvc color coded sleeves. Cylinder MS powder coated bracket with chain for 4 cylinder. Silicon tubes and standard fittings 1/4".	2 sets
(ii)	Aluminum cage with 16 gauge aluminum section and ACP panel and grills for covering gas cylinders with steel stand (4'X8'X1')	1 unit
(iii)	Replacement of existing 3 sided anti room and fabrication, erection of new structure from three lateral sides (One side fixed wall) and top ceiling. Cabin size 6'X4'X8'. Aluminum pipe section 16 gauge (JINDAL make) and protective oxide layer by electrolytic process. 5 mm clear Teflon glass and 4 mm noncombustible polyethylene core manufactured to relevant IS standard. Cabin consist of 2 No of sliding door on opposite side (7'X2.5') with locking arrangement. LED light and all other fittings for a fully functional unit.	1 unit
(iv)	Providing and fixing homogeneous minimum 3.0 mm thick PVC sheets (size of 3'X6" type) or equivalent on floor and skirting in approved pattern on a smooth and damp proof base using rubber based adhesive of approved quality like Fevicol SR 998 including leveling small undulation with POP if required rolling with light wooden roller weighing 5 kg.	600 Square feet
(v)	Cover for windows made of horizontal rolling sheets of 2 mm stiff cloth that can be rolled up and down with necessary accessories to support the structure. Size 4'X5'.	6